



U<sub>w</sub> 0,78W/m<sup>2</sup>K







ENVIQ is a modern MD system with an installation depth of 81 mm and a third flexible center seal, offering extended reinforcement chambers to increase the windows' rigidity. Thanks to its optimum profile height, the system provides up to 5% more light than other solutions in its class. Moreover, it includes transition profiles for large sliding and balcony doors and allows the use of bonded glass technology, increasing stability and enabling the creation of larger structures.

- A 5-chamber system with an installation depth of 81 mm with a third flexible center seal.
- Multiple glazing packets 24 53 mm possible Widened reinforcement chambers to increase window stiffness and allow for the execution of all properly designed structures.
- Optimum profile folding height giving up to 5% more light compared to to other systems in its class (in a double-sash window with a width of 1465 mm and height of 1435 mm).
- Includes transition profiles for large sliding and balcony doors.
- In this system, it is possible to use pasted glass technology, which increases the stability of the windows and makes it possible to build larger structures.
- A wide range of decorative foils.

## Profile available in a wide range of colour and wood-imitating veneers















1401



504700



3002



Colours close to original due to print technology

and many others

 $Uw = 0.78 [W/m^2K]^*$ 

\*for a reference window 1230 mm x 1480 mm with a glazing package, 4/18/4/18/4 with Ug=0,5 W/m2\*K with the Swisspacer Ultimate